

SSAW Dredging Steel Pipe



Technical Specifications

Length	Random length / 5.8m / 6m / 11.8m / 12m or as per customer's requirement
Ends	Beveled / Straight cut ,Plastic or Material ends protectors
Size range	529-630mm
Wall thickness	6.0-12.0mm
OD	219-3500mm
Material	X70, X65, X60, X42,GR.B, Q235, Q195, 20#, 10#, 45#,Q345B
Main standard	API5L, ASTM A252, ASTM A53, GB/T 8163
Surface Treatment	Black painting / Vanish painting / 1PE / 3PE / FBE coated
Application Range	Dredgingproject,Petroleum, Chemical, Election Power, Oil&Gas, Shipbuilding, Water-treatment, etc
Marking	According to standard or according to the customers requirement
Certification	ISO9001, CE, API5L etc
The Third Party Inspection	SGS and other party alloyed by clients



SSAW Dredging Steel Pipe in Workshop



Painting



Testing equipment

Chongqing Hi-Sea Marine Equipment Import&Export Co.,Ltd.

Address: 20-5,General Chamber of Commerce Building, No.2 Hongjin Street, Yubei District, Chongqing, China

Email: machine@hiseamarine.com mitang0708@foxmail.com **Skype:** cncqtang **QQ:** 2278612160

TEL: +86-23-67032301 **FAX:**+86-23-67955123 **Mobile:** +86-18108354610 **Post Code:**401147

Website: www.hiseamarine.com www.chinahisea.com