

Floating Discharge Hose



Floating discharge hose features:

- 1.Outer cover with excellent abrasion resistance and UV protection.
- 2.Wearing colored indicator layer.
- 3.Single foam floatation casing,preventing water absorption.The hose emergence above water is not less than 20% of the total volume.
- 4.High quality,wear resistant rubber.
- 5.Flange design according to customers' request.
- 6.Bending angle:in working condition,the bending angle is from 0° to 45° .

TECHNICAL SPECIFICATIONS

Inter diameter(mm)	500	600	700	800	900	1000	1100
Working pressure(Mpa)	1.2	1.5	1.5-2.5	1.5-2.5	1.5-2.5	1.5-2.5	2.5

Note: Other technical parameter can be made according to the client's requirement.



DN800 floating discharge hose

Chongqing Hi-Sea Marine Equipment Import & Export Co.,Ltd.

Add:15F,Jinshan Matrix A, Saidi Rd., New North Zone, Chongqing , China, 401122.

Tel: +86-23-67304326 EXT8016 **Fax:** +86-23-67956622(manual) **Mob:** +86-18108354610 +86-15215103815

Email: dredge-component@foxmail.com machine@hiseamarine.com

Website: www.hiseadredge.com www.chinahisea.com www.hiseamarine.com